

**URIMAT®**

Swiss quality – since 1998.

URIMAT Schweiz AG  
Etzelstrasse 39  
CH-8634 Hombrechtikon

+41 (0)55 251 52 30  
info@urimat.com  
www.urimat.com



# FX-M WASH PLACE UNIT Clean & Dry

## FX-M wash place unit „Water-Soap-Air“

FX-M wash place unit Water-Soap-Air for wall mounting, touch free opto-electronically controlled. For hot and cold water connectivity. Thermostat for mounting onto angle valve with installation set for preset delivery of premixed hot water, soap pump for liquid soap and hand dryer. Lighting up of pictograms above the respective sensor position as well as start of wash place lighting indicate user detection. The pictogram of the active function is illuminated maximally. Cabinet housing made of powder coated stainless steel, white, mirrored door, door hinge left and cylinder lock.

Soap tank not in scope of delivery.

Dimensions 600 x 900 x 205 mm (W x H x D)

### TECHNICAL DATA


Minimum flow:	pressure 1.0 bar
Volume of water flow:	6 l/min at 3 bar flow pressure
Supply voltage:	230 V AC, 50/60 Hz
Overall power:	1200 W
Protection Degree:	IP20
Soap pump flow time:	0.1-25.5 s
Hand Dryer Air Volume:	80 m <sup>3</sup> /h = 22 l/s
Hand Dryer Air Velocity:	95-115 m/s

Article Number: 85.451



### Recommended sink for FX-M washbasin unit

The Quadro-FX single washbasin is suitable for single-user installation:



As a tailor-made washbasin solution for row installation  
From our Varius range, choose the ETON trough with a back wall.  
The washbasins are made of Miranit, a synthetic resin-bonded mineral material.

